



型号	BT30ERT BT30RT		BT28ERT BT28RT		BT26SERT BT26SRT		BT26ERT BT26RT		BT24ERT BT24RT		BA28ERT BA28RT		BA24ERT BA24RT		
类型	直臂式										曲臂式				
尺寸															
最大工作高度	30.30m	28.60m	26.70m	26.32m	24.80m	28.10m	24.30m								
最大平台高度	28.30m	26.60m	24.70m	24.32m	22.80m	26.10m	22.30m								
最大水平伸距	22.70m	21.30m	19.20m	18.90m	17.30m	18.80m	16.50m								
整机长度(收拢状态) A	12.25m	11.66m	10.83m	10.82m	10.25m	11.83m	9.83m								
整机长度(装箱状态)	11.96m	11.82m	11.12m	10.77m	10.81m	12.03m	10.03m								
整机宽度(收拢状态) B	2.50m														
整机宽度(装箱状态)	2.28m														
整机高度(收拢状态) C	2.89m														
整机高度(装箱状态)	2.57m														
工作平台尺寸(长×宽)	2.44m×0.9m														
转台尾摆	1.61m														
最小离地间隙 D	0.41m														
轴距 E	2.8m														
最小转弯半径(内轮/外轮)	1.87m/3.22m														
轮胎	385/45-28														
最大跨越高度											9.14m				
最大下探深度											6.61m		4.03m		
性能															
安全工作载荷(不受限/受限)	300kg/454kg		454kg				250kg		300kg						
最大工作人数	3										2				
最大爬坡能力	30%	45%	30%	45%	30%	45%	30%	45%	30%	45%	30%	45%	30%	45%	
收拢状态最大行驶速度	6km/h														
起升状态最大行驶速度	1.1km/h														
底盘工作最大允许角度	X-5°/Y-5°														
转台回转角度	360°连续														
平台摆动角度	180°														
小臂变幅角度	130°	135°	130°	135°											
重量															
整机重量	18900kg	18400kg	16600kg	16090kg	14300kg	18300kg	17100kg								
动力															
动力源	 锂电池 520Ah/80V 充电器 5kW/80V,12V					 柴油发动机 Deutz TD2.9 L4 55.4kW									
液压油箱	150L														

